

## Vegetative to Flower Spectrum



450 Watt - 24" x 18" x 6", 22 lbs



600 Watt - 24" x 22" x 6", 30 lbs

# Aegis Series S3

### 450W or 600W

#### SYSTEM SPECIFICATIONS

Grow-It-LED's S3 Vegetative to Flower Spectrum offers high efficiency warm and cool white diodes coupled with 660nm red for proper plant physiological growth. See spectral distribution page for more information on this spectrum's performance characteristics

### SPECTRUM CONTROL (One of 2 Options Required)

Casambi wireless spectrum control for smart phone or manual spectrum control with potentiometer dial. Casambi wireless control also includes scheduling and daily light integral capabilities.

#### CONSTRUCTION

Robust aluminum housing for durability, custom built heatsink for optimal heat dissipation, cooling fans for increased LED performance and extended life, manual on-off switch, internal power quick disconnect, internal disc themistor for heat protection.

#### **MOUNTING**

Eye bolts for cable or chain attachment (standard). 4 point rachet cables or Gripple Y-Fit toggle cables purchased separately.

#### **RATINGS & WARRANTY**

Temperature rated from - 40°F to 95°F, service life > 100,000 hours (L90), built to UL 1598 standard, BAA & RoHS compliant. 5 year product warranty. Consult factory for extended warranties.

| Ordering Informat | ion        |                 |               |                             |                       |                   |
|-------------------|------------|-----------------|---------------|-----------------------------|-----------------------|-------------------|
| AEG               | <b>S3</b>  |                 |               | MSC or WSC                  |                       |                   |
| Series            | Spectrum   | Power           | Voltage       | Spectrum Control            | Cord & Plug           | Housing Color     |
|                   |            |                 |               |                             |                       |                   |
| Aegis Series      | Vegetative | L = Low (450W)  | U = Universal | WSC = Wireless              | C? = Cord             | WH = White        |
|                   | to Flower  | H = High (600W) | (120-277v)    | Spectrum Control<br>Casambi | ? = Specify Length    | BK = Black        |
|                   |            |                 |               |                             | P? = Plug             | Consult Factory   |
|                   |            |                 |               | MSC = Manual                | ? = Specify NEMA Type | For Custom Colors |
|                   |            |                 |               | Spectrum Control            |                       |                   |
|                   |            |                 |               | Potentiometer               |                       |                   |
|                   |            |                 |               |                             |                       |                   |

#### **Mounting Accesoies**

Grow-It-LED offers an assortment of custom options ranging from unique fan colors, housing colors, branding logos, custom mounting, controls for spectrum tuning and more. We are open to new ideas and encourage our customers to show their creative

**Custom Options** 




4PR = 4 Point Rachet Cables GRP = Gripple Y Fit Cables

# **Spectral Analysis**


### Aegis Series S3 - Vegetative to Flower Spectrum



Vegetative Spectral Distribution



Flower Spectral Distribution



| Technical Information          | 450W Veg.     | 450W Flower   | 600W Veg.                  | 600W Flower  |  |  |  |
|--------------------------------|---------------|---------------|----------------------------|--------------|--|--|--|
|                                | 120v = 1.5A   | 120v = 3.78A  | 120v = 2.05A               | 120v = 5.15A |  |  |  |
| Operating Voltage and Current  | 277v = .65A   | 277v = 1.64A  | 277v = .89A                | 277v = 2.23A |  |  |  |
| Operating voltage and current  | 347v = .52A   | 347v = 1.31A  | 347v = .71A                | 347v = 1.78A |  |  |  |
|                                | 480v = .37A   | 480v = .95A   | 480v = .51A                | 480v = 1.3A  |  |  |  |
| Cooling Fan Power Draw         | 12w           | 12w           | 15w                        | 15w          |  |  |  |
| LED Power Draw                 | 143w          | 463w          | 231w                       | 603w         |  |  |  |
| Fixture PPF (380-780nm) umol/s | 414           | 1133          | 597                        | 1460         |  |  |  |
| Total Power Draw               | 155w          | 475w          | 246w                       | 618w         |  |  |  |
| Heat Output (BTU)              | 617.6         | 1549.11       | 839.39                     | 2108.7       |  |  |  |
| Efficiency umol/J              | 2.7           | 2.4           | 2.7                        | 2.4          |  |  |  |
| Driver Efficiency              | 95%           |               |                            |              |  |  |  |
| Warranty                       | 5 Years       |               |                            |              |  |  |  |
| Dimensions                     | 25.20"L x 21. | 95"W x 4.47"H | 25.20"L x 21.95"W x 4.47"H |              |  |  |  |
| Weight                         | 25 lbs        | 25 lbs        | 30 lbs                     | 30 lbs       |  |  |  |

| Spectrum Information        | 450W Veg. | 450W Flower | 600W Veg. | 600W Flower |
|-----------------------------|-----------|-------------|-----------|-------------|
| TOTAL 380nm - 850nm umol/s  | 414       | 1133        | 597       | 1460        |
| Blue 400nm - 499nm umol/s   | 129.4     | 162.7       | 120.4     | 217.2       |
| Red 600nm - 699nm umol/s    | 134.1     | 476.7       | 243.8     | 612.3       |
| FarRed 700nm - 759nm umol/s | 2.6       | 29          | 9.3       | 36.1        |

All information provided is subject to change. Check our website or contact us for updated information.